SEAMASTER
7700 WALLTEX EMULSION PAINT

PRODUCT DESCRIPTION

Seamaster 7700 Walltex Emulsion Paint is an economical high quality copolymer emulsion paint formulated for interior wall surfaces. Walltex provides a solid matt finish with effective hiding. For best result, new walls should be suitably primed with 1700 WS wall sealer. It has good alkaline and fungus resistance.

USES

For the protection and decoration of all interior masonry and renderings; including plasters, cements, asbestos, brickworks, hard and soft boards.

PHYSICAL CHARACTERISTICS

Ingredient	:	Modified acrylic emulsion, mineral extenders, pigments and additives
Solvent	:	Water
Density	:	1.50-1.60 (kg/litre)
Solid	:	Approximately 55 %
Viscosity	:	105 5 KU (at 27 0.5°C)
Coverage	:	10-12 m^2/litre
Colours	:	Refer to colour card
Gloss	:	Matt

PROPERTIES

Recommended Dry Film Thickness : 25-30 microns per coat

Drying Time	:	Touch dry	:	15 minutes
		Hard dry	:	30 minutes
Recoating Interval	:	2 hours		

SURFACE PREPARATION

New Masonry Surface :

It is crucial that ample time is allowed for the concrete/plaster surfaces to dry out. High moisture content is a common cause for premature paint failures, such as blistering, discolouration, etc. Concrete/plaster are alkaline in nature and together with the presence of salts and moisture may cause paint systems to fail prematurely.

Old Unpainted/previously Painted Masonry Surface :

Surface must be dry and free from any structural damaged and cracks. Wash the surface to remove any stains, debris and powderiness before application with 7700 Walltex Emulsion Paint.

APPLICATION METHOD

Method of Application	:	Brush or roller
Product Preparation	:	Ready for use after thoroughly stirring. However, if thinning
is		required, not more than 10 % of water may be added for
the		first coat. For best result, thinning is not recommended for
the		subsequent coats.